

特性 Characteristics

种类 Designation	型式 Model	负荷 Rating	微动开关形式 Type of switch enclosed & contact arrangement	电缆种类 / 长度 Cable type / length	触点 Contact type	动作压力 Action force	外壳材质 Material of Rind
小型脚踏开关 Mini type	TFS-201	10A 250VAC	V-15 微动开关	0.5mm2,3C/1 meter(米) ~3 meter(米)	1A1B	0.7kg	塑胶 Plastic
	TFS-01	10A 250VAC	V-15 微动开关	0.5mm2,3C/1 meter(米) ~3 meter(米)	1A1B	0.7kg	塑胶 Plastic
	TFS-1	10A 250VAC	V-15 微动开关	0.5mm2,3C/1 meter(米) ~3 meter(米)	1A1B	0.9kg	铁壳 Iron
标准型 - 点动式 Standard type Momentary Action	TFS-101	10A 250VAC	V-15 微动开关	0.75mm2,3C/0.5 meter(米),1.1 meter(米) ~3 meter(米)	1A1B	1.2kg	塑胶 Plastic
	TFS-102	15A 250VAC	TM-1704	0.75mm2,3C/1 meter(米),1.5 meter(米) ~2 meter(米)	1A1B	1.1kg	
	TFS-2	10A 250VAC	V-15 微动开关	0.5mm2,3C/1 meter(米) ~3 meter(米)	1A1B	1.1kg	铝合金 Aluminum Cast
	TFS-3	10A 250VAC	V-15 微动开关	0.75mm2,3C/0.5 meter(米),1.1 meter(米) ~3 meter(米)	1A1B	1.2kg	
	TFS-3S	15A 250VAC	TM-1704	0.75mm2,3C/1 meter(米),1.1 meter(米) ~3 meter(米)	1A1B	1.1kg	
标准型 - 交替式 Standard type Alternate action	TFS-105	6A 250VAC	TS-105	0.75mm2,2C/1 meter(米),1.1 meter(米) ~2 meter(米)	PUSH ON PUSH OFF	2kg	塑胶 Plastic
	TFS-402	15A 250VAC	TM-1704		1A1B	3.2kg	铝合金 Aluminum Cast
大型 - 无护罩型 Large type- None protective guard	TFS-404	15A 250VAC	TM-1704 x 2		2A2B	3.2kg	
	TFS-802	15A 250VAC	TM-1704	附电缆固定头, 不附电缆 Accessory: Cable gland (No cable)	2*1A1B	3.2kg	
	TFS-302	15A 250VAC	TM-1704		1A1B	3.2kg	
大型 - 半护罩型 Large type- Top protective guard	TFS-304	15A 250VAC	TM-1704 x 2		2A2B	3.2kg	
	TFS-702	15A 250VAC	TM-1704		2*1A1B	3.2kg	
大型 - 全护罩型 Large type- Protective guard	TFS-502	15A 250VAC	TM-1704		1A1B	3.2kg	
	TFS-504	15A 250VAC	TM-1704	2A2B	3.2kg		
	TFS-602	15A 250VAC	按钮弹簧式 Button spring type	2*1A1B	2.8kg		

触点类型见 P28 与 P31。Contact types refer to P28 and P31  
带电缆的种类, 标配长度为 1m。

外观和尺寸 Appearance and Dimension

TFS-101  
TFS-102  
TFS-105



TFS-2




TFS-3  
TFS-3S



外观和尺寸 Appearance and Dimension

TFS-502  
TFS-504



TFS-602

